

Distinctive by design.

First choice for education and healthcare

Built at an ideal height for both adults and children the B3 also features an ultra-hygienic touch-sensitive control panel, the biggest dispense area in its class for bottles and a tamper-proof rear cover guard for safety.

Reasons to choose

- Ultra-hygienic touch sensitive control panel
- High-capacity dispense area for bottles and jugs
- Integrated cup dispenser
- Sealed, hygienic, direct-chill cooling system
- Sparkling water option



Distinctive by design.

Water system



Direct Chill

Configurations



Countertop



Floorstanding







Distinctive by design.

Water options







Sparkling

Available colours







Black

borgandoverstrom.com

Borg & Overström Totality™



Driven by a relentless pursuit of excellence, Borg & Overström Totality™ is a research and development methodology for the advancement of hygiene, innovation and technology in refreshment systems.



impact resistant epoxy resin panel finish
Providing an increased level of hygiene and longevity,
Fynil™ is a scratch and impact resistant epoxy-resin surface finish - effectively resisting biofilm development and limescale cohesion.

Biofilm, limescale and



World-class filtration
For the ultimate drinking
experience, Borg & Overström
appliances can be pre-fitted
with a 3M filter to reduce
sediment, chlorine, odours
and scale.





Laboratory certified 99.99% bacteria-free Every Borg & Overström appliance undergoes an anti-microbial, antipathogen, sanitising procedure. The reassurance of hygienically safe appliances is provided by the unique bacteria-eliminating process, Sterizen™.



Ultra-violet sterilising system
For added hygiene confidence,
appliances can be fitted with
Viovandt™ – an ultra-violet
sterilisation process that
reduces water-born bacteria.


b3

borgandoverstrom.com

B3 models
Power requirements Hertz 50/Volts 220-240
Chilled temperature Min 2°C/Max 11°C
Hot temperature Max 92°C
Throughput litres per hour Chilled & Sparkling 30/Hot of

Countarian	147.1	ь.				
Countertop W325xD380xH475mm	Water system	Dispense height	Max power consumption	Silver	White	Black
Chilled & Ambient	Direct Chill	265mm	100W	104001	104002	104003
Chilled, Hot & Ambient	Direct Chill	265mm	550W	104011	104012	104013
Floorstanding W325xD380xH1065mm	Water system	Dispense height	Max power consumption	Silver	White	Black
Chilled & Ambient	Direct Chill	265mm	100W	104021	104022	104023
Chilled, Hot & Ambient	Direct Chill	265mm	550W	104031	104032	104033
Chilled, Ambient & Sparkling	Direct Chill	265mm	140W	104051	104052	104053
Chilled, Hot & Sparkling	Direct Chill	265mm	640W	104041	104042	104043

Distinctive by design.



Additions for B3





Environmentally-friendly situations where an integral cup disposable cups designed to fit Borg & Overström cup dispensers perfectly.



Deep Sparkle™ CO² refills

Can be disposed via standard steel recycling or general waste. Requires CO² regulator with gauge.



Sanitisation kit

Six monthly sanitising cycles ensure appliances function at the optimum hygiene levels.



Waste kit overflow sensor

Featuring an audible highwater level alarm to prevent the waste tank from overflowing.



Cup dispenser blanking panel

Replacement top panel for

dispenser is not required.

Leak detection kit

shuts the water supply in the unlikely event of a leak.



Install kit with 3M filter

Featuring a moisture sensor that Install appliances simply and effectively in a wide range of applications. Complete with a 3M filter.



Ultra-violet filter kit

Complete Viovand t^{TM} filter kit to assist in water purification and removal of unwanted micro-organisms.



Wall bracket kit

For added security, use the wall bracket set to anchor your watercooler back to the wall. Simple to fit and unobtrusive.



Rear cover kit

Tamper-proof rear cover anchors the appliance to the wall and protects plumbing and electrical connections. Ideal for public areas.

Distinctive by design.

Book a visit to the Borg & Overström Academy for a personal demonstration of the new B3

Talk to an adviser +44 (0) 1362 695 006 sales@borgandoverstrom.com

borgandoverstrom.com

Version: B3.08.18.UK (ENG)